

MULTIMEDIA DATA/VIDEO PROJECTORS

Contrast
2000:1

Brightness
2000lm

Long Life Lamp
— with lamp low mode —
5000h

SVGA M O B I L E
P R O J E C T O R

ES100U

A portable model

That's easy to set up for instant viewing.

Adds another dimension to lessons.






ES100U

MOBILE SVGA PROJECTOR



Input and Output Terminals




- 1 RGB In 2
- 2 RGB Out 1
- 3 Audio In
- 4 Audio Out
- 5 Remote IR
- 6 S-Video
- 7 Composite Video
- 8 RS-232C
- 9 USB

Specifications

Model	ES100U
Display technology	0.55"1-chip DMD,12deg.DDR, DDP2000
Resolution	800 600 (total 480,000 pixels), 600 video lines
Brightness	2000lm (Lamp Low Mode 1400lm)
Contrast	2000 : 1
Picture size	40" ~ 300" (100" = 3.5m)
Source lamp	200W (Shut Off Time 5000Hrs) with Low Mode 250W (Shut Off Time 2000Hrs)
Computer compatibility	VGA® ~ XGA® (640 480 ~ 1024 768), True: 800 600, Sync on green available
Video compatibility	NTSC / NTSC 4.43 / PAL (including PAL-M, N) / SECAM / PAL-60 Component Video; 480i/p(525i/p), 576i/p(625i/p), 720p(750p), 1080i(1125i 60Hz), 1080i(1125i 50Hz), [1080i(1250i 50Hz) is not available]
PC input terminals	RGB: mini D-sub 15pin 2 Audio: Stereo mini jack (ø 3.5 mm) 1
Video input terminals	Video: RCA 1 S - video 1, Audio: RCA (L,R) 2
Output terminals	RGB: mini D-sub 15pin 1, Audio: Stereo mini jack (ø 3.5 mm) 1
Communication terminals	RS - 232C (8pin) 1 (Direct command is available), USB terminal for Page Up / Down
Audio speaker	2W mono
Fan noise	32dBA (Lamp Low Mode)
Dimension W H D	310 100 245 mm (excluding height adjustment)
Weight	2.9kg / 6.5lbs
Power supply	AC100 - 240V / 10%, 50 / 60Hz
Optional lamp	VLT-XD400LP


*Windows is a registered trademark of Microsoft Corporation. *Macintosh is a registered trademark of Apple Computer Inc. *SXGA, XGA and SVGA are registered trademarks of IBM Corporation.*All brand names and product names are trademarks, registered trademarks or trade names of their respective holders.
*DLP (Digital Light Processing) is a trademark of Texas Instruments.

Dimensions



Screen size and Projection distance

As seen from the side



Screen size chart 4:3 aspect ratio

Screen						Distance from screen (L)					
Diagonal size		Width (W)		Height (H)		Maximum Zoom		Minimum Zoom		Height projected image (Hd)	
inch	cm	inch	cm	inch	cm	inch	m	inch	m	inch	cm
40	102	32	81	24	61	54	1.4	65	1.7	7.0	17.8
60	152	48	122	36	91	81	2.1	99	2.5	10.5	26.7
80	203	64	163	48	122	109	2.8	132	3.4	14.0	35.6
100	254	80	203	60	152	137	3.5	165	4.2	17.5	44.5
150	381	120	305	90	229	206	5.2	249	6.3	26.3	66.7
200	508	160	406	120	305	275	7.0	332	8.4	35.0	89.0
250	635	200	508	150	381	345	8.8			43.8	111.0
300	762	240	610	180	457	414	10.5			52.5	133.0

The above numbers are approximate, and may be slightly different from the actual measurements.

MITSUBISHI ELECTRIC CORPORATION
HEAD OFFICE: MITSUBISHI DENKI BLDG., 2-2-3, MARUNOUCHI, CHIYODA-KU, TOKYO 100-8310, JAPAN

To find out more about ES100U and our projectors, visit us at
Global.MitsubishiElectric.com/projectors/